

# TP6/S

## CUTTING BENDING FORMING MACHINE FOR AXIAL COMPONENTS FOR SURFACE MOUNTING

### EXAMPLES OF FORMS



### 25.OLO1 STANDARD


The TP6/S machine is designed for cutting and bending axial components for surface mount. The standard version offers the most common dimensions. Special versions to customer's specifications are available upon request. It is however necessary to know all dimensions of the component, before and after the bending operation.



PRODUCTION/HOUR

TAPED: 50000

LOOSE: 5000



	MM		IN	
	min	max	min	max
<b>P</b>	12	47	.472	1.850
<b>C</b>	1,5	10	.059	.388
<b>L</b>		40		1.574
<b>D</b>	0,4	16	.015	.629
<b>d*</b>	0,6 fix		.023 fix	
<b>B*</b>	2 fix		.078 fix	
<b>h*</b>	2,5 fix		.098 fix	

# TP6/S OPTIONAL ACCESSORIES

---



BR6 - 400200 REEL HOLDER

---



MOT98 - 7915030 - 220 V. - MOTOR DRIVE UNIT  
MOT98 - 7915031 - 110 V. - MOTOR DRIVE UNIT.

---



TNS - 21.0011 WASTE TAPE EJECTOR

---



CS10 - 51.0100 FEEDER FOR LOOSE COMPONENTS

---



200240 COMPLETE BODY GUIDE

---