



EcoStrip 9380

Welcome to the Future of Entry Level Cut & Strip

- Three in one transport unit
- Improved price to performance ratio
- Simple machine operation thanks to Schleuniger's standardized S.ON user interface
- The latest technology, cleverly combined with Schleuniger's industry renowned precision

CUT & STRIP

EcoStrip 9380



Simply Capable

Transforming your expectations: Get a machine with flexible, «all in one» roller-, belt- and short mode transport drives.

Cut your cost, strip your efforts: The machine is economically priced, yet in terms of performance, it exceeds previous models by 20 percent.

Explore simplicity: Simple machine operation thanks to Schleuniger's standardized S.ON user interface with 5.7" color touchscreen.

Precision has a name: All driven axes are powered by our proven *Bricks* electronic platform.



The EcoStrip 9380 capabilities are significantly expanded due to quick change transport unit for rollers, belts and short mode processing.

Compatible with a wide range of accessories (prefeeder, marking, stacking, coiling and tying) for future expansion.

Minimize training and setup time with S.On software. Cayman and S.WOP compatible for integration into various networks.

Technical Specifications	
Max. cable outer diameter	8.0 mm (0.31")
Max. cable cross section standard	0.05 – 8 mm ² (10mm ² EN60228 class 5&6) AWG 8
Blade sets usable up to x mm	1 x 12 mm (1 x 0.47")
Feeding system	Rollers or Belts
Single conductor (1 step)	Yes
Multilayer	Yes
Max wire or cable length	1'000'000 mm (39.370")
Pull off length left side	46 mm (1.18")
Pull off length right side	152 mm (5.98")
Short mode up to	46 mm (18 mm measured on remaining insulation length)
Interfaces	Standard: Ethernet for PC, USB Optional: SMI (I/O's), Prefeeder, Wire marker (HS), Inkjet printing, Stacker / Coiler
Power Supply	100-240 VAC
Dimensions (L x W x H)	435 x 397 x 360 mm (17.1 x 15.6 x 14.2 ")
Weight	25 kg (55.1 lbs.)