



Innovators in Wire Processing

CoaxStrip 5200
Coaxial Cable Stripping Machine

STRIPPING

CoaxStrip 5200

Technical Specifications

Max. Cable Diameter	7 mm (0.276")
Diameter Increments	0.01 mm or 0.001"
Wire Cross Section	0.032 - 6 mm ²
Max. Stripping Length	33 mm (1.30")
Stripping Length Increments	0.01 mm or 0.001"
Max. Stripping Steps	3
Cable Clamping	Programmable clamping force
Cycle Time	≥ 4,2 s (depending upon cable type and programming)
Production Rate	max. 650 pcs./h (depending upon cable type and programming)
Program Capacity	1000 cables
Interfaces	Foot pedal, USB „Host“
Noise Level	< 70 db (A)
Power Supply	100/115 VAC, 230/240 VAC, 100 VA, 50/60 Hz
Dimensions (L x W x H)	390 x 130 x 280 mm (15,3 x 5.1 x 11")
Weight	10 kg (22 lbs.)
CE-Conformity	The CoaxStrip 5200 complies fully with all CE and EMC equipment guidelines relative to mechanical and electrical safety and electromagnetic compatibility.
Important Note	Schleuniger recommends that wire samples be submitted in cases where there is doubt as to the processing capabilities of a particular machine.

Sales and Service by:

Schleuniger Group
Thun | Switzerland
www.schleuniger.com

To Be Precise.